

# ePMP™ Force 300-25



Wireless service providers and enterprises around the globe are challenged to deliver reliable connectivity in overcrowded RF environment. As spectrum increasingly becomes a scarce commodity, finding the right broadband connectivity solution is vital for all low and high density types of deployments.

Cambium Networks resolves this challenge with a breakthrough technology solution that delivers superior performance, resiliency and reach in the most congested environments. Combining the latest 802.11ac Wave 2 chipset and the field proven TDD MAC of ePMP, the Force 300-25 offers a compelling yet affordable point to point product and a high gain subscriber module for the ePMP3000 and ePMP 3000L Access Points.

Force 300-25 continues the tradition of previous products with an integrated 25dBi dish with a narrow beamwidth and reliable mechanics. Supporting peak throughput up to 600 Mbps, the Force300-25 also supports an always on spectrum analyzer.

## FEATURES:

- Cambium Networks' ePMP Force 300-25 is designed to operate in high interference environments and provides superior throughput of over 500 Mbps of real user data.
- The ePMP Force 300-25 supports channel size configuration from 20MHz up to 80MHz and modulates up to 256 QAM.
- The ePMP Force 300-25 supports constant monitoring of the radio spectrum with a built-in always-on spectrum analyzer.
- Configurable modes of operation ensure robust adaptivity to both symmetrical and asymmetrical traffic while providing high performance and round-trip latency as low as 3-5 ms.
- QoS management offers an outstanding quality for triple play services - VoIP, video, and data - and provides three levels of traffic priority.
- Long deployment range is enabled by a high gain antenna combined with 27dBm of transmit power.
- Installation is a breeze with the included wall and pole mounting bracket.

## SPECIFICATIONS

### SPECTRUM

Channel Spacing	Configurable in 5 MHz increments
Frequency Range	Wide Band Operation 4910 - 5970 MHz (Note: Allowable frequencies and bands are dictated by individual country regulations.)
Channel Width	20   40   80 MHz

## SPECIFICATIONS

### INTERFACE

MAC (Media Access Control) Layer	Cambium
Proprietary Physical Layer	2x2 MIMO/OFDM
Ethernet Interface	10/100/1000 BaseT, Compatible with Cambium PoE & Standard PoE pinouts
Protocols Used	IPv4/IPv6 (Dual Stack), UDP, TCP, ICMP, SNMPv2c, NTP, STP, IGMP, SSH
Network Management	IPv4/IPv6, HTTPs, SNMPv2c, SSH, Cambium Networks CnMaestro™
VLAN	802.1Q with 802.1p priority

### PERFORMANCE

ARQ	Yes
Nominal Receive Sensitivity (w/FEC) @20 MHz Channel	MCS0 = -87 dBm to MCS8 (256 QAM-3/4) = -63 dBm (per chain)
Nominal Receive Sensitivity (w/FEC) @40 MHz Channel	MCS0 = -85 dBm to MCS9 (256QAM-5/6) = -59 dBm (per chain)
Nominal Receive Sensitivity (w/FEC) @80 MHz Channel	MCS0 = -82 dBm to MCS9 (256QAM-5/6) = -56 dBm (per chain)
Modulation Levels (Adaptive)	MCS0(BPSK)to MCS9 (256QAM5/6)
Transmit Power Range	0 to +27 dBm (combined, to regional EIRP limit) (1 dB interval)

### PHYSICAL

Surge Suppression	1 Joule Integrated (C000000L065A - 30V Gigabit surge suppressor is recommended for optimum protection)
Environmental	IP55
Temperature	-30°C to +60°C (-22°F to +140°F)
Weight	2.4 kg (5.3 lbs)
Wind Survival	180 km/hour (112 mi/hour)
Dimensions (Dia x Depth)	47 cm x 31 cm (18.5 in x 12.2 in)
Pole Diameter Range	6.4 cm – 7.6 cm (2.5 in – 3 in)
Power Consumption	12 Watts
Input Voltage	30 Volts Nominal (14V to 30V range)
Power Method Supported	30V Cambium PoE Injector (included)

### SECURITY

Encryption	128-bit AES (CCMP mode)
------------	-------------------------

### CERTIFICATIONS

FCCID	Z8H89FT0017
Industry Canada Cert	109W-0017
CE	EN 301 893 V2.1.1 (5.4 GHz), EN 302 502 V2.1.1 (5.8 GHz)

### PART NUMBER

### DESCRIPTION

C058910C102A	ePMP Force 300-25 5 GHz High Gain Radio (FCC) (US Cord)
C050910C104A	ePMP Force 300-25 5 GHz High Gain Radio (IC) (Canada/US Cord)
C050910C203A	ePMP Force 300-25 5 GHz High Gain Radio (EU) (EU Cord)
C050910C303A	ePMP Force 300-25 5 GHz High Gain Radio (EU) (UK Cord)
C050910C001A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (no Cord)
C050910C101A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (US Cord)
C050910C201A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (EU Cord)
C050910C301A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (UK Cord)
C050910C401A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (India Cord)
C050910C501A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (China Cord)
C050910C601A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (Brazil Cord)

# SPECIFICATIONS

PART NUMBER	DESCRIPTION
C050910C701A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (Argentina Cord)
C050910C801A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (ANZ Cord)
C050910C901A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (South Africa Cord)
C050910CZ01A	ePMP Force 300-25 5 GHz High Gain Radio (RoW) (No PSU)
ANTENNA SPECIFICATIONS	5 GHZ SPECIFICATION
Frequency Range	4910 - 5970 MHz
Antenna Type	Dish
Peak Gain	25 dBi
3dB Beamwidth-Azimuth	6-10 degrees
3dB Beamwidth-Elevation	6-10 degrees
Front-To-Back Isolation	25 dB
Cross Polarization	20 dB

# ANTENNA PATTERNS

