

CLG

4G/Multiband & GNSS Puck Antenna

Features

- Low Profile Puck Antenna
- 1 x 4G/LTE/Multiband element
- 1 x GPS/GLONASS active element
- Screw Mount

Specifications

	4G Multiband	GPS/GLONASS
Frequency range	690-800/ 800-960 / 1710-2170 / 2500-2700 MHz	1575.42 MHz /1602MHz
Peak Gain	1 / 2.5 / 3.8 / 5 dBi	4 dBi (typical)
Polarisation	Linear	RHCP
VSWR	<3.0:1	<1.5:1
Power rating	10 W	10W
Impedance	50 Ohms	50 Ohms
LNA Gain		27 dB (typical)
Noise Figure		1.0 dB (typical) (2.0 max)
Input Voltage		2.5-5.0V DC
Power Consumption		30 mA (max)
Dimensions	102 x 33.5mm (dxh)	

Ordering Options

FCLG35311-SMSM-1K	CLG antenna with 2 x 1M RG174 and SMA-Male
FCLG35311-SMSM-2K	CLG antenna with 2 x 2M RG174 and SMA-Male

Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK

Tel: +44 (0)1280 824055
Fax: +44 (0)1280 817179
Email: sales@ead-ltd.com
Web: www.ead-ltd.com