

		AQ	-	T	2	1	5	-	P	X	X	X	A	X	A	-	X	X	X
Model																			
T	Voltage regulating IED																		
Device size																			
1	1/4 of 19" rack																		
Analog measurement																			
5	5 Current measurement channels and 4 voltage measurement channels																		
Mounting																			
P	Panel mounted																		
Auxiliary voltage																			
H	80...265 VAC/DC																		
L	18...72 VDC																		
Measurement accuracy																			
0	Power/Energy measurement accuracy 0.5%																		
2	Power/Energy measurement accuracy 0.2%																		
Terminals																			
A	Standard																		
B	Ring lug terminals																		
Reserved for future use																			
A	N/A																		
Digital inputs on power supply module																			
A	3 Digital inputs , 24 V nominal threshold																		
B	3 Digital inputs , 110 V nominal threshold																		
C	3 Digital inputs , 220 V nominal threshold																		
D	2 Digital inputs , 24 V nominal threshold																		
E	2 Digital inputs , 110 V nominal threshold																		
F	2 Digital inputs , 220 V nominal threshold																		
Reserved for future use																			
A	N/A																		
Slots C, E, F (3 pcs)																			
A	Empty																		
B	8 Digital inputs																		
C	5 Output relays **																		
D	Arc protection with 4 point sensor channels, 2 x HSO, 1 x BI *																		
F	8 x RTD input **																		
G	2 x RJ-45 100Mb Ethernet & IRIG-B * / ***																		
H	2 x ST 100Mb Ethernet & IRIG-B * / ***																		
I	4 x mA outputs - 1 x mA input **																		
J	Double LC 100Mb Ethernet (HSR, PRP redundant protocols) * / *** / ****																		
K	Double RJ45 100Mb Ethernet (HSR, PRP redundant protocols) * / ***																		
L	RS-232 - Serial fiber (Plastic-Plastic) * / ***																		
M	RS-232 - Serial fiber (Plastic-Glass) * / ***																		
N	RS-232 - Serial fiber (Glass-Plastic) * / ***																		
O	RS-232 - Serial fiber (Glass-Glass) * / ***																		
* One card at most per IED																			
** Two cards at most per IED																			
*** Can only be applied to the last slot																			
**** Can't be applied when type "L" (18...72 VDC) auxiliary voltage is selected																			