

		AQ	-	F	2	1	5	-	P	X	X	X	A	X	A	-	X	X	X
	Model																		
F	Feeder protection																		
	Device size																		
1	1/4 of 19" rack																		
	Analog measurement																		
5	5 Current measurement channels and 4 voltage measurement channels																		
	Mounting																		
P	Panel mounted																		
	Auxiliary voltage																		
H	80...265 VAC/DC																		
L	18...72 VDC																		
	Measurement accuracy																		
0	Power/Energy measurement accuracy 0.5%																		
2	Power/Energy measurement accuracy 0.2%																		
	Terminals																		
A	Standard																		
B	Ring-lug current terminals																		
C	Standard current terminals, spring cage voltage and I/O terminals																		
D	Ring-lug current terminals, spring cage voltage and I/O terminals																		
	Reserved for future use																		
A	N/A																		
	Digital inputs on power supply module																		
A	3 Digital inputs, 24 V nominal threshold																		
B	3 Digital inputs, 110 V nominal threshold																		
C	3 Digital inputs, 220 V nominal threshold																		
D	2 Digital inputs, 24 V nominal threshold																		
E	2 Digital inputs, 110 V nominal threshold																		
F	2 Digital inputs, 220 V nominal threshold																		
	Reserved for future use																		
A	N/A																		
	Slots C, E, F (3 pcs)																		
A	Empty																		
B	8 Digital inputs																		
C	5 Output relays (max. 2 pcs)																		
D	Arc protection with 4 point sensor channels, 2 x HSO, 1 x BI (max. 1 pcs)																		
F	8 x RTD input (max. 2 pcs)																		
G	2 x RJ-45 100Mb Ethernet & IRIG-B (max. 1 pcs) *																		
H	2 x ST 100Mb Ethernet & IRIG-B (max. 1 pcs) *																		
I	4 x mA outputs - 1 x mA input (max. 2 pcs)																		
J	Double LC 100Mb Ethernet (HSR, PRP redundant protocols) (max. 1 pcs) *																		
K	Double RJ45 100Mb Ethernet (HSR, PRP redundant protocols) (max. 1 pcs) *																		
L	RS-232 - Serial fiber (Plastic-Plastic) (max. 1 pcs) *																		
M	RS-232 - Serial fiber (Plastic-Glass) (max. 1 pcs) *																		
N	RS-232 - Serial fiber (Glass-Plastic) (max. 1 pcs) *																		
O	RS-232 - Serial fiber (Glass-Glass) (max. 1 pcs) *																		

* Can only be applied to the last slot