AQ - T 2 5 7 X - P X X X A X A - X X X X X X X X X

Model

T	Transformer protection

Device size

5	1/2 of 19" rack

Analog measurement

7	10 Current and 4 voltage measurement channels

Function package

A	Standard
B	Standard + Automatic Voltage Regulator function

Mounting

P	Panel mounted

Auxiliary voltage

H	80...265 VAC/DC
L	18...72 VDC

Measurement accuracy

0	Power/Energy measurement accuracy 0.5%
2	Power/Energy measurement accuracy 0.2%

Terminals

A	Standard
B	Ring-lug current terminals
C	Standard current terminals, spring cage voltage and I/O terminals
D	Ring-lug current terminals, spring cage voltage and I/O terminals

Reserved for future use

A	N/A

Digital inputs on power supply module

A	3 Digital inputs, 24 V nominal threshold
B	3 Digital inputs, 110 V nominal threshold
C	3 Digital inputs, 220 V nominal threshold

Reserved for future use

A	N/A

Slots F, G, H, I, J, K, L, M, N (9 pcs)

A	Empty
B	8 Digital inputs
C	5 Output relays (max. 6 pcs)
D	Arc protection with 4 point sensor channels, 2 x HSO, 1 x BI (max. 1 pcs)
F	8 x RTD input (max. 2 pcs)
G	2 x RJ-45 100Mb Ethernet & IRIG-B (max. 1 pcs) *
H	2 x ST 100Mb Ethernet & IRIG-B (max. 1 pcs) *
I	4 x mA outputs - 1 x mA input (max. 2 pcs)
J	Double LC 100Mb Ethernet (HSR, PRP redundant protocols) (max. 1 pcs) *
K	Double RJ45 100Mb Ethernet (HSR, PRP redundant protocols) (max. 1 pcs) *
L	RS-232 - Serial fiber (Plastic-Plastic) (max. 1 pcs) *
M	RS-232 - Serial fiber (Plastic-Glass) (max. 1 pcs) *
N	RS-232 - Serial fiber (Glass-Plastic) (max. 1 pcs) *
O	RS-232 - Serial fiber (Glass-Glass) (max. 1 pcs) *
Q	2 x SFP 100Mb Ethernet & IRIG-B (max. 4 pcs) **
R	3 x High-speed high current output (max. 3 pcs)
T	4 x mA inputs - 1 x mA output (max. 2 pcs)

* Can only be applied to the two last slots.

** Can only be applied to the four last slots. Requires an SFP adapter. See "Accessories" list.