AQ - T 2 5 6 A - P X 8 X A X A - X X X X X X X X X X

Model

T Transformer protection

Device size

5 1/2 of 19" rack

Analog measurement

6 10 Current measurement channels

Functionality package

A Standard

Mounting

P Panel mounted

Auxiliary voltage

H 80...265 VAC/DC
L 18...72 VDC

Measurement accuracy

8 N/A

Terminals

A Standard
B Ring lug terminals

Reserved for future use

A N/A

Digital inputs on power supply module

A 3 Digital inputs, 24 V nominal threshold
B 3 Digital inputs, 110 V nominal threshold
C 3 Digital inputs, 220 V nominal threshold

Reserved for future use

A N/A

Slots E, F, G, H, I, J, K, L, M, N (10 pcs)

A Empty
B 8 Digital inputs
C 5 Output relays ****
D Arc protection with 4 point sensor channels, 2 x HSO, 1 x BI *
F 8 x RTD input **
G 2 x RJ-45 100Mb Ethernet & IRIG-B * / ***
H 2 x ST 100Mb Ethernet & IRIG-B * / ***
I 4 x mA outputs - 1 x mA input **
J Double LC 100Mb Ethernet (HSR, PRP redundant protocols) * / ***
K Double RJ45 100Mb Ethernet (HSR, PRP redundant protocols) * / ***
L RS-232 - Serial fiber (Plastic-Plastic) * / ***
M RS-232 - Serial fiber (Plastic-Glass) * / ***
N RS-232 - Serial fiber (Glass-Plastic) * / ***
O RS-232 - Serial fiber (Glass-Glass) * / ***

* One card at most per IED
** Two cards at most per IED
*** Can only be applied to the two last slots
**** Five cards at most per IED